SMART Business Division





SMART Business Division



- **S**anitization Tunnel
- Mask
- **Approved disinfectant**
- Robot's
- Thermal scanner/Face Recognition Solution's

"Challenges Provides a Survival Instinct"

"Prevention is Better than Cure"



SMART Business Division



- Euromax Personal Care Division, a Unit of EUROSTAR Group based in Dubai, UAE has complied with authorities to prevent the spread of epidemics by introducing several product and solutions in this domain.
- We in Eurostar Group felt our networks across GCC and African markets can offer the SMART Business Solutions
- Eurostar Group as wealth of knowledge and expertise in health technology and allied Business Segments



ST360 - Sanitization Tunnel



Application

Shopping Malls | Schools | Universities | Hospitals | Labour Camps | Factories | Big Offices | Airport | Metro | Hotels | Apartments | Warehouses etc..





ST 360 Standard Model



Specification

Size (L x W x H)	1m x 1.2m x 2.2m	
Frame	MS powder coated steel frame	
Cladding	2mm thick MS powder coated sheet	
Motion Sensor	Yes	
Flooring	3mm thick checker plate/ Rubberized Mat	
Water Tank	120L	
Nozzles	Nickel Plated	
	Hole size: 0.2mm	
	Max pressure: 100bar/1000 psi	
	Connection(inch): 10/24	
Pressure Pump	1.5HP	
Weight	450Kg	
Pipe	9mm high pressure flexible pipe	
Spray Sanitizer chemical	Approved Disinfectant	
Plastic curtain	Yes	
Light	Yes	
Shipment 20/40	8/18nos	
Wheels	75mm dia high duty wheels	
Spray duration/sec	10sec	
Water consumption	0.5L/min	
Power consumption	220-230VAC	

- ▶ The Branding can be done based on customer requirement's.
- ▶ The Tank Capacity also can be made into 500 and 1000Litres.
- ▶ Thermal Screening Solution can also be provided separately.

USP

- The Sanitization Tunnel is MADE IN UAE.
- The Unit is made out of MS Steel and ACP.
- Its Very Durable and made for Outdoor and Indoor installations.
- We provide One year Warranty.
- Installation and Training is Free.
- We also make Custom design Tunnels.
- After Sales Support
- · AMC
- Can Provide Export Pack and How to assemble kit.
- SS Food Grade 305 also available for catering and F&B facilities.

ST360SS - Sanitization Tunnel



Sanitization Tunnel

Food Grade SS304

PRODUCT FEATURES

- Long lasting construction
- Motion sensor system
- Approved disinfectant
- Heavy duty engineered product

Applications:

- Industrial Kitchens
- Restaurants
- Hotel
- Catering Facilities
- Food Processing Units
- Fruit and Vegetable Processing
- Bakeries
- Ice Cream Factories



Height- 220cm

Width-108cm

Depth-100cm

PIR Sensor

Nozzles 14 Nos.

Toughend Glass Window

Drain Points

Built in Tank: 25Ltrs or 100Ltrs

Heavy Duty Flooring Sheet

High Power Motor

Food Grade Compliant




TS300 - Smart Thermal Scanner Station




Access control system with

- Forehead Temperature Measurement
- Recognition Mask Recognition



7"Monitor





1x Thermal imaging sensor

24 x LED white light LED fill light can help camera system to shoot. Can fill the scene according to the actual situation.

2 x LED Infrared Light

Better capture of images at night to achieve more uniform light on the screen

1.2 mm thick tempered glass

High-definition clear picture quality, no dropped frames, color balance.

7 inch IPS HD screen

Clear picture quality in HD No dropped frame color balance

All aluminum body

Integrated aluminum alloy forming process to achieve uniform heat dissipation.

Application















Functions and Features

Accurate Temperature Measurement Error of plus or minus 0.3 °C

Two-eye recognition Support two-eye live human face detection

Mask Detection

No need to remove the mask, automatically capture the face for identification

Fast recognition

200ms face recognition

30.000-Person Face

Support 30,000 local face storage

High Recognition Rate

Face recognition accuracy rate is as high as 99.5%

Built-in fill-in light, low-light situations applicable

Embedded Systems

Low power consumption, high stability

Backstage Management

Abnormal records, equipment management, personnel management

Mobile APP

Visitor management, information push

Ensure safety during resumption of production Combat the epidemic effectively

Temperature error range ± 0.3 °C

Detect body temperature accurately, intelligent warning in case of fever

Normal body temperature (

Hypothermia (1)

High body temperature (8)

37 3°C-38 5°C 36.0°C-37.3°C

More than 38.5°C





Access Control System with Face Recognization TS250 -**Temperature Measurement Function**



- Industrial Grade Identification Accuracy
- Face recognition + High Resolution Thermal Imaging temperature and Measurement Calibration



Product Features



INFRARED TEMPERATURE MEASUREMENT

100 MS complete the temperature test (@within 1 meter), +or- 3°C temperature measurement accuracy (@ ring temperature 20-30°C), suitable for indoor windless environment



HIGH TEMPERATURE ALARM

Real time sound and light alarm of temperature anomaly, dual authorization of face recognition and temperature measurement, control rapid passage



FACE RECOGNITION

200MS accurate face recognition, 50,000 face database, effectively prevent photos, video and other illegal attacks

Product Development



Hospital

MOBILE TERMINAL, WE MANAGEMENT

Timely upload the identity information with body temperature, body temperature warning value background and APP can be set.

Application Scenario












Face recognition temperature measuring terminal Scenic Spot



- The attendance management
- · Organizational structure

The APP end

- · Equipment management
- Attendance statistics
- · Access Control

The PC side manages the background

Visitor System






- · Approval Management
- · Parameter setting

Thermal Scanner System Stand





Specifications

Table bracket

2xUSB: 1x LED light

Stand size: 283(L)x260(W)x38(H)mm

Weight: 1.8 Kgs

55*40*37CM 10PCS/CTN

Floor Pole bracket, 60CM

2xUSB: 1x LED light

Stand size: 283(L)x260(W)x600(H)mm

Weight: 13.7Kgs

Floor Pole bracket, 110CM

2xUSB: 1x LED light

Stand size: 283(L)x260(W)x1100(H)mm

Weight: 9 Kgs

122*31*34CM, 4PCS/CTN




UV Blaster-UVC Light Based Room Disinfection



◆ CHEMICAL FREE UV-DISINFECTION

◆ FAST & EFFICIENT DISINFECTION





Non contact Faster Surface Disinfection Based on UVC



360° illumination



360° Sensors for human safety



Audio & Visual Safety Alarm



Wireless 10m Operating Distance



Android & Windows based Operation



Easy to Carry

The UV-Blaster Disinfection is so versatile that it can disinfect a 12 x 12 feet room in 10 minutes. The built-in timer is programmed in hours and minutes. You can customize sanitization time depending on the size of the room. The system can be controlled remotely via Android & Windowed based operation.

Parameter	Specification
Total UV Output	250 Watts
UV Tube	6 Nos
Operation	Android / Windows
Connectivity	100 meter wireless
Current	220 VAC, 50Hz
Power Consumption	800Watts
Lamp Life	10000 Hours
Dimension	H 1900 x L 400 x W 400 mm
Weight	≤ 35 Kgs

The UV-Blaster can be used for the following environments or wherever microbial disinfection is required:

- Nursing Homes, Clinic Outpatient Surgery Centers Physicians Offices, Ambulance
- Patient Rooms, Waiting Rooms Testing Laboratories, Operation Theater
- Ventilator Clinics & Kennels Passenger Flights &, Bus, Train & Metro
- Airport, Metro Station & Banks
 Schools-Classrooms, Food Processing
- Detention Centers, Homeless Shelters Shopping Complex, Movie Theaters
- Hotel Rooms, Lockers Rooms



UV Blaster

Professional Thermal Camera



Professional Thermal Camera for Shopping Malls & Large Traffic Areas



TC1000

- ♦ Face Detection, Body Temperature Detection, and Face Capture
- ♦ Abnormal temperature alarm: High temperature limit, Low temperature limit, Zone temperature difference alarm
- ♦ Support global temperature measurement and regional temperature measurement
- **♦ Temperature Accuracy**

Target temperature 35°C A 38°C ±0.3 °C Target temperature 20°C A 33°C ±0.6 °C Target temperature 38°C A 50°C ±0.6 °C

- ♦ Face snapping: support simultaneous detection of 20-30 faces (accurate 5-8 faces)
- ♦ Installation height: 2 M Face distance: 2 M
- ♦ Support H.265 + / H.265 / H.264 + MJPEG double encoding, triple stream
- ♦ Accuracy: without black body ± 0.5 degrees, with bold-body ± 0.3 degrees;
- ♦ Single IP solution, rich network expansion capability, easy to access various video monitoring platforms

API: ONVIF (Profile S, Profile G, Profile T), SDK



- ♦ Face Detection, Body Temperature Detection, and Face Capture
- ♦ Abnormal temperature alarm: High temperature limit, Low temperature limit, Zone temperature difference alarm
- ♦ Support global temperature measurement and regional temperature measurement
- **♦ Temperature Accuracy**

Target temperature 35°C A 38°C ±0.3 °C Target temperature 20°C A 33°C ±0.6 °C Target temperature 38°C A 50°C ±0.6 °C

- ♦ Face snapping: support simultaneous detection of 20-30 faces, Built-in 50.000 face database:
- Installation height: 2 M Face distance: 5 M
- ♦ Support H.265 + / H.265 / H.264 + MJPEG double encoding, triple stream
- ♦ Accuracy: without black body ± 0.5 degrees, with bold-body ± 0.3 degrees;
- ♦ Single IP solution, rich network expansion capability, easy to access various video monitoring platforms

API: ONVIF (Profile S, Profile G, Profile T), SDK



Super Oxidized Disinfectant Solution



NADES

ECA (Electro Chemically Activated) Solution/Disinfectant to safe and improve the microbial quality of water, food, environment and surface area. This environmentally friendly disinfectant is produced by the electrolysis of natural ingredients (water and salt (NaCl) only.

One For All. Perfect form of Disinfection. (Kills 99.99% of Germs)



Applications of NADES

Water Treatment	Surface Disinfection	Product Microbial Decontamination
Drinking water treatment	Floor/Wall/Tables	Fruit/Vegetable sanitation
Process water treatmentSwimming pool water treatment	 CIP/Machines Filler head microbial decontamination 	Fish microbial decontaminationCarcass washing
 Cooling tower water treatment Waste/Sewerage water treatment Lake water treatment Irrigation water treatment 	Bottle rinsing Reused bottles rinsing Water pipeline and water system flushing Tank disinfection Utensils/Equipment	Meat/Sea Food microbial decontamination

NADES Disinfectant Liquid is recommend for the Tunnels 1:3 is the ratio of dilution, So basically every 25 Litres of DL add 75 Litresof water.

DM approved.

German Technology

MADE IN UAE Since 2017



ASD100 - Automatic Sanitizer Dispenser






ASD100

Specifications: If you choose the dispenser of gel/liquid

Induction Way:	Infrared reflection	
Induction Distance	e: The shortest 3CM The longest 10 <u>+</u> 2CM	
Material:	ABS, PP	
Capacity:	1000ml	
Refillable Liquid:	Milky Liquid	
	(Such as: Shampoo, Shower Gel, Hand Soap etc)	
Dispensing:	Gel/Liquid	
Dose:	():0.8ml ()():1.6ml	
Battery:	4 or 8 AA Alkaline Bateries	
Power Adapter:	Input Voltage AC100~240V 50/60Hz	
Output Voltage:	DC6.0v 2A (Optional, It is not included by default)	









How we work?



- Eurostar Group has been always a pioneer in the Electronics and Technology Domain for more than 4 Decades
- Our expertise and wealth of knowledge with commitment to provide excellent products has been the hallmark of success.
- Our Mantra is Scout/Sell/Service
- Value for Money and understanding the Customer needs
- We also provide Reseller Program mechanism for the Smart Business Solutions
- We are flexible and adaptable.

Completed Projects













Eurostar General Trading LLC

PO Box: 27403, Dubai, UAE 33, Vision Tower, Business Bay, Dubai, UAE

Tel: 00-9714-4514444

www.euromaxpersonalcare.com

www.eurostargroup.com